



READ ALL RULES !

EDGE MOTORSPORTS DEMOLITION DERBY

F.S. Open Mod 2009

"Each driver and mechanic has an obligation to read the rules for their best interest"

RULES AND REGULATIONS – FULL SIZE OPEN MODIFIED

IMPORTANT: Each driver and mechanic must sign in at registration desk the day of show and have their cars inspected solely to determine compliance with those rules (and not for purpose of determining safety of car or participant) at least 90 minutes prior to show time or he will be ineligible to run! NO REFUNDS!

DRIVER MUST ATTEND DRIVERS' MEETING PRIOR TO DEMOLITION DERBY OR DRIVER WILL BE DISQUALIFIED.

I have read the rules and acknowledge to have received a copy of same and agree that the decision of the Judges is final. I agree to participate at my own risk absolutely. It is a condition of my participation in the contest that I sign a further release of liability in the form to be supplied by Edge Motorsports and I agree to sign such a release.

SPECIAL NOTICE: NO ALCOHOL OR DRUGS ALLOWED IN ANY RESTRICTED (PIT, HOLDING OR PERFORMING) AREA. ANY VIOLATIONS WILL RESULT IN DISQUALIFICATION OF CAR, DRIVER AND CREW. NO REFUNDS !!!

The Edge Motorsports Demolition Derby is promoted as an unusual spectator attraction.

DRIVERS and MECHANICS are subject to and must obey the following rules and regulations which are set up by the promoter and the track where this event is being held:

- 1. Each driver must be a minimum age of 16. All 16 & 17 year olds must have a parent or guardian sign an insurance waiver.
2. Each driver must fill out an entry blank. All drivers must supply their own cars. ONLY ONE ENTRY PER PERSON. Cars cannot be double entered.
3. Edge Motorsports or promoter reserves the right to approve or reject any and all entries.
4. Only drivers and mechanics who sign the release sheet will be permitted in the pit area or on the track. Driver and one (1) pit person receive free pit passes upon registration of car on day of show.
5. Contestants of the Edge Motorsports Demolition Derby are not employees of the track, fair association or the promoter of the Edge Motorsports Demolition Derby.
6. Edge Motorsports, the promoter, track owner or fair association will not be held responsible for any cars, parts or personal property before, during and after the show.
7. NO PHOTOCOPYING OF ENTRY FORMS. All entries are to be filled in and signed by driver at fair office (or designated area) and entry fee paid at time of entry. Any driver changes must be made at fair office 24 hours prior to event.

REGISTRATION PROCEDURE – ENTRY FORMS

Entry must be made in the name of the driver who will actually drive the car in the event.

If the driver who is entered cannot drive, the DRIVER DOES NOT have the right to resell the entry form to someone else.

At the discretion of Edge Motorsports and/or the Fair Board, the entry may be sold back to the Fair Board, who will in turn sell it to the next person on its waiting list. This option will become available only after the entry forms are completely sold out.

A driver does not have the right to specify whom his entry form will be sold to at any time.

Type of Car – DO NOT REMOVE VIN #

- 1. Any hardtop automobile or station wagon with a wheelbase of 106" or larger.
2. NO trucks, convertibles, jeeps, vans, hearses, limousines or checker cabs, Chrysler Imperials, Windsors, or Imperial Sub-frame cars.
3. Cars previously run in demos may be considered too battered and unsafe, resulting in disqualification.

RUNNING

- a. Risk: Demolition derbies are hazardous and high-risk sports; therefore, anyone with a health condition, i.e., concussion, heart problems etc. or who is pregnant should not compete.
b. Disqualification: 1. Open Door 2. Fires 3. Unsafe vehicle 4. Non-working fire extinguisher 5. Special situation deemed necessary by official.
c. Body Protectors – Protect yourself. Work Boots, sport equipment – e.g. neck brace, knee pads, shoulder pads, hip pads etc. are recommended.
** No bare exposed skin. All drivers must wear long pants/coveralls and long sleeved shirts.
d. Working seat belt and racing helmet are mandatory. Goggles or face shields are recommended.
e. BRAKES – VEHICLES MUST HAVE DEPENDABLE BRAKES AND MUST BE WORKING PROPERLY BEFORE ENTERING PEN AT ALL TIMES. All boundaries must be observed.
f. NO DRINKING OF ALCOHOLIC BEVERAGES ON TRACK, EMERGENCY VEHICLE AREA OR IN THE PIT AREA. Any driver or pit person under the influence of alcohol or drugs will be immediately disqualified and removed from the grounds. This will be strictly enforced.
g. No cars permitted in the competition area before the heat in which they are to participate.
h. Competitive aggressive hits! Sandbaggers will be disqualified!
i. All cars are to be removed from the fairgrounds or racetrack immediately following the show.
j. Additional safety regulations may be imposed, depending on track and conditions.
k. ALL DECISIONS OF THE OFFICIAL ARE FINAL.

NO CHANGES OR ALTERATIONS OF RULES MAY BE MADE EXCEPT BY EDGE MOTORSPORTS NO REFUNDS.

NO CARS LEFT FOR JUNK!!!

DERBY TECH DEPT. edgederbytech@hotmail.com 705-953-9196

cut 2009

cut

cut

Detach and keep with entry fee. DO NOT GIVE OUT

F.S. Open Mod 2009

EDGE MOTORSPORTS DEMOLITION DERBY OFFICIAL ENTRY BLANK

Show Date _____ Entries limited to the first _____ cars

Location _____

I have read the rules and acknowledge to have received a copy of same and agree that the decision of the Judges is final. I agree to participate at my own risk absolutely. It is a condition of my participation in the demolition derby that I sign a further release of liability in the form to be supplied by Edge Motorsports and I agree to sign such a release. I agree to have my car at the race area and sign in at least 90 minutes prior to show time and attend drivers' meeting or I will be disqualified and ineligible to run!

Driver's Name (print) _____ Age (must be at least 16) _____

Street Address (print) _____ Tel: _____

City (print) _____ Postal Code: _____

Email: _____

Date: _____ Signed _____

Signature of Driver

Entry Fee \$ _____ Includes GST to accompany entry NO CHEQUES Only cash or money orders payable to EDGE MOTORSPORTS will be accepted.

All entry fees to Edge Motorsports

Requested Car Number _____

NO REFUNDS!

PREPARATION OF CAR – REMOVE OR CONVERT THE FOLLOWING PRIOR TO ARRIVING AT FAIRGROUNDS OR TRACK

1. RIDING ON CAR	Insurance Regulation: No person riding on outside of cars at anytime
2. FLAMMABLE MATERIAL	Seats & trim - All must be removed from the vehicle except driver's seat.
3. TRAILER HITCH	Must be removed and all sharp edges must be mashed down prior to derby event.
4. GLASS/AIRBAGS	All windows, mirrors, airbags & trim, must be removed prior to derby event.
5. DOORS & NUMBERS	Driver & Passenger doors must be PAINTED WHITE. An optional roof number plate may be securely installed.
6. FIRE EXTINGUISHER	Must be within reach of the driver, must work and have a working gauge.
7. BATTERY	One 12 volt car battery must be moved to front passenger floor board and securely fastened in a box/container clear of all fuel sources. Following inspection it must be covered with a non-flammable shield.
8. GAS TANK	Stock gas tanks must be removed. Must be a steel marine tank, custom steel fuel tank, or certified racing fuel cell. No plastic tanks. All tanks must be securely fastened down (bolted) in the middle of the back seat area. Tank must be covered with a non-flammable material after inspection. Maximum 3 gallons gas. Referee has final decision.
9. FUEL LINES	All fuel lines must have leak proof fitting with steel or rubber lines (no clear lines). No exceptions. Lines should run inside car.
10. ELECTRIC FUEL PUMP	Must have a safety shut off switch (punch button), marked in red located on roof in center of the windshield area for officials use.
11. FUEL SYSTEM	Electric fuel pump must be isolated with a non-flammable material covering lines, tank & pump. Non-flammable covering may be fire resistant blanket or air bag material.
12. HOOD	Hoods are not mandatory. Without hood – use electric fan only - fans directly connected to motor must be removed. With hood - a 12" opening must be cut in hood over carburetor (not over fan). Hoods must remain open for officials' inspection. Hood must be fastened down in maximum of 6 places with seat belt strapping, wire, 1/4" chain only, or bolted to fender. Following inspection one wire may be ran from center of hood to bumper as the 6 th spot. Hood latch should be removed. No welding hoods.
13. TRUNK	Trunk/tailgate to be fastened down in same way as hood or may be welded using 6 – 3" square plates. If trunk is welded a 16" square hole must be cut in top of trunk for officials' inspection.
14. BODY PANELS	Metal may be cut from around wheels for clearance. Front & rear quarter panels may be bolted with up to 5 bolts per panel - maximum 3/8" bolt.
15. DOOR FASTENING	Driver's door may be welded solid. All other doors must be fastened shut with wire, straps, 1/4" chains or spot-welded 1" every 12" or 6 – 3" square plates welded on per door. Solid driver's door window screens are not recommended.
16. BRACING	Outside of car may have a 12" X 72" X 1/4" max steel plate applied to driver & passenger doors, bolted in 4 locations (with a maximum 1/2" through bolt) & spot welded 1" every 12". Bevel should not exceed 20°. NO "C" CHANNEL OR ANGLE IRON. Not mandatory.
17. ROLL BAR	Single roll bar up each doorframe, inside or across outside of the roof. Roll bars going across the roof must be through bolted twice through the roof for driver & spectator safety. This roll bar may be welded or bolted to the frame or rockers. An additional bar may be added behind the seat welded or bolted from roll bar to roll bar. Recommend 3" to 4" square tubing or pipe. No excessive use of materials. Not mandatory.
18. WINDSHIELD SPACE	Must have a minimum of a single steel bar or chain from the cowl to the roof bolted or welded. The "A" or "H" style protection is permissible but the bars must look like the A or H. The cross brace must be in the middle and in no way come in contact with the distributor protector. The horizontal bar must be a minimum 8" from cowl. If using the "A" it may be welded or bolted in 3 locations. If using the "H" it may be welded or bolted in 4 locations & be no more than 36" in width. Driver must not be impaired from exiting through window area of car in case of emergency.
19. DASH BAR	Min 3" to Max 4" square tubing mounted doorframe to doorframe, but not to firewall. Not Mandatory. Driver Safety.
20. INTERIOR MODIFICATIONS	No welding of any inside body support seams or firewall seams. All holes in firewall must be covered with a non- flammable material. Large holes in car floors must be repaired with same gauge metal and securely fastened. No reinforcement.
21. BUMPERS	CAR BUMPERS ONLY, to be used. Front & rear bumpers may be reversed. Front & rear bumpers may be mashed in so not to catch on other cars. Bumpers may be wired in 4 locations to rad cradle & trunk. Bumper shocks may be reinforced with flat bar or tubing to help keep bumpers on. Excessive use of material will be asked to be removed. No loading of bumpers. Officials may request a hole be made in bumper for inspection. Bumper layers may be welded together. No metal added.
22. FRONT GRILL	No screens allowed. (Stock A.C. condensers permitted in original position.)
23. RADIATOR	Must be flushed of anti-freeze and replaced with water only. Overflows must point straight down or positioned so not to harm other drivers & spectators. Floating rad cradles with maximum 1/8" gauge steel angle or flat bar will be allowed – Absolutely no reinforcement to frame or rad cradle.
24. TRANSMISSION COOLER	Is permitted and must be secured in engine compartment. Transmission dipstick must be securely fastened, wired down or have an overflow tube pointing straight down away from drivers or spectators. OR May be re-located to directly behind driver seat, bolted to the back bar and completely covered to the floor with a tin shroud. A minimum of two 1" holes must be made in the floorboard directly below cooler for drainage. Hoses must run straight down under driver seat and be completely covered with non-flammable material. Hose spec: 2500psi single braid hydraulic hose with pressed fittings only, must be rated for 250°F+. Hydraulic hoses must be marked as such by manufacturer. Hydraulic hoses must have pressed fittings only. No other fittings acceptable.
25. DISTRIBUTOR	May be protected. Fresh cars must have 1" away from the firewall. Excessive material will be asked to be removed.
26. SUSPENSION	Suspension must remain stock (movement must occur). Broken or sagging parts may be replaced. It is recommended that rear coil be wired or welded to differential. No spring blocks or added helpers. Rear ends can be exchanged (5 bolt pattern car rear ends). Rear control arms can be changed (Ford/Mercury, '98+, 6 control arms, stock material; pre '98 – 4 control arms, stock material). Rear differential cannot be reinforced. Gears may be welded. Steering columns, drive shafts and rear sway arms may be altered but not reinforced. Ball joints, tie rods, control arms and steering linkage must remain stock. NO REINFORCING ALLOWED. Trailing arms must be made of trailing arm material- no square tubing material. No truck rear ends.
27. HEADERS	Must be secure, must point upwards and not at other drivers/spectators. Must be a reasonable length or will be asked to be cut or removed. Official's discretion.
28. FRAMES	No welding of frame seams top or bottom. Rusty or bent frames may be repaired with steel no thicker than factory and no longer or wider than 4" on 2 sides only. Over repaired frames will be considered reinforced and will result in alteration or disqualification. Official's discretion. No painting of frames except for the following. Frame repairs must be painted bright orange before arriving for derby event. All repairs to frames must be reported to officials before inspection – over-repaired frames will be asked to be cut – if not - may result in disqualification.
29. DRIVETRAIN PROTECTORS	Protectors may only be fastened to motor or transmission (NO FASTENING TO FRAME OR BODY).
30. DIFFERENTIAL PROTECTORS	Are permitted. Must only be bolted on to the differential. Housing tubes may be welded.
31. MOTOR MOUNTS	Stock mounts may be welded or chained. Home-made mounts are acceptable. Any excessive or added mounts will result in disqualification.
32. BODY MOUNTS	All rubber stock body mounts and stock size bolts must stay in place. Increasing bolt size is not allowed. Max flat washer size – 3". Four (4) additional body mounts up to 3/4" inch threaded rod are allowed, placed strategically where desired or replace existing body mounts. Two threaded rods are allowed for the rad cradle that is not included in the additional 4. Two extra bolts may be added to drivers compartment for safety.
33. TIRES	Maximum 16" D.O.T. Tires must be low aggression. No forklift tires or solid fill tires. All tires must be filled with air only. Tires may be doubled. No split rims. No screwing tires to rim or studding. All wheel weights must be removed and no welding stem protections. Carry spare 16" D.O.T. mud tires in case track conditions warrant. Referee's discretion.
34. PRE-BENDING	Regular Season – May be bent within reason. Can be deemed unsafe to other drivers resulting in alteration or disqualification. Doors may be rolled - 1" of weld every 12" max. Trunks may be tucked. Wagon roofs may be pre-bent so rear end lifts but not crushed to make sides fold inwards thereby creating a ramp. Modifications deemed unsafe will be disqualified. Williams Cup Championship – No pre-bending - No rolling doors – Car must be fresh.

"Official's Decision is Final"

Monitor www.edge-motorsports.ca for any new rule updates/inclusions/restrictions.

Derby Tech Dept.

edgederbytech@hotmail.com

705-953-9196

